

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In Re application of

**Komatsu HIROSHI**

Art Unit: **2871**

Application No.: **To Be Assigned**

Examiner: **M. Ton**

Date Filed: **October 22, 2001**

For: **Liquid Crystal Display**

**PRELIMINARY AMENDMENT**

Commissioner of Patents  
Washington, D.C. 20032

Sir:

Preliminary to the examination of the above-identified application, the following amendments and remarks are respectfully requested.

**IN THE ABSTRACT:**

Please **AMEND** the Abstract of the Disclosure to read as follows (Exhibit I is a marked up version of the amended Abstract):

**ABSTRACT OF THE DISCLOSURE**

A liquid crystal display including: a first transparent substrate coated with a first alignment layer, a second transparent substrate coated with a second alignment layer, the second substrate facing the first transparent substrate, a liquid crystal layer between the substrates, a polarizer attached on the outer surfaces of the substrates, a pair of electrodes formed on the first substrates, and a driving circuit applying signal voltage to the electrodes. The liquid crystal molecules adjacent to the first substrate is rotated by applying the voltage,

102201 06828650

but, the liquid crystal molecule adjacent to the second substrate is fixed regardless of the applied voltage. The electrode pair, substantially straight data and common electrodes, are inclined at an angle with respect to a gate line.

**IN THE SPECIFICATION:**

Please **AMEND** the Specification to read as follows (Exhibit II is a marked up version of the amended Specification):

**Page 2, paragraphs three and four, starting with line 10.**

Conventional TFT LDCs (thin film transistor liquid crystal display) have a drawback known as a viewing angle dependency, that is, the contrast ratio is changed according to the viewing angle. This has made it difficult to apply the technology to a large size display.

To solve this problem, various liquid crystal displays have been proposed, such as a retardation attaching TNLCD (twisted nematic liquid crystal display) and a multi-domain liquid crystal display. The LCDs still have other technical problems such as complicated production process and shifting color tones.

**Page 3, paragraph one, starting with line 2.**

Recently, an IPS LCD has been introduced to obtain a wide viewing angle. This technology is discussed in JAPAN DISPLAY 92, p547, Japanese patent application No. 7-36058, Japanese patent application No. 7-225538, and ASIA DISPLAY 95, p707. As shown in FIG. 1a and FIG. 1c, in the liquid crystal layer 12 the molecules are aligned at a 45° angle. The principal transmittance axis of a polarizer 9 attached to the first substrate 1 is the same direction as the alignment direction of the liquid crystal 12, and the principal transmittance direction of an analyzer 10 attached to the second substrate 5 is perpendicular to the

FOIA b7 - DECLASSIFIED

alignment direction of the liquid crystal layer 12. A pair of electrodes 2, 3 is formed on the first substrate 1.

**Page 6, paragraph five, starting with line 16.**

FIG. 4a shows a plan view of the liquid crystal display according to the present invention, and Fig. 4b shows a cross-section of the device taken along the line IV-IV of Fig. 4a;

**Page 8, paragraph two, starting with line 12.**

The liquid crystal molecules 78 will be twisted between the two substrates 26, 27 by applying the driving voltage to the electrodes 48, 49. The distance between two adjacent electrodes 48, 49 is less than the thickness of the liquid crystal layer 60. The retardation value is calculated by following formula:

$$\lambda/2 < \Delta n d \leq \lambda.$$

**Page 9, paragraph one, starting with line 3.**

FIG. 3 shows optical axes of the liquid crystal display according to the present invention.  $\theta_{EL}$  is represented as the extension direction of the electrodes 48 and 59,  $\theta_{FE}$  is the electric field direction applied by the electrodes,  $\theta_{LC1}$  is the optical axis direction of the liquid crystal molecules adjacent to the first substrate and  $\theta_{LC2}$  is the optical axis direction of the liquid crystal molecules adjacent to the second substrate when the voltage is not applied.  $\theta_{PL1}$  is the principal transmission axis of a polarizer,  $\theta_{PL2}$  is the principal transmission axis of an analyzer,  $\theta_{LC1}$  is the optical axis direction of the liquid crystal molecules adjacent to the first substrate when the voltage is applied. The alignment direction  $\theta_{LC1}$  of the first substrate is anti-parallel to the alignment direction  $\theta_{LC2}$  of the second substrate, and the principal transmission axis  $\theta_{PL2}$  of the analyzer is parallel to the alignment direction  $\theta_{LC1}$ ,  $\theta_{LC2}$ . In

FOIA b 7 - DECLASSIFIED

addition, the principle transmission axis  $\theta_{PL1}$  of the polarizer is perpendicular to the principal transmission axis  $\theta_{PL2}$  of the analyzer.

**Page 10, paragraph one, starting with line 3.**

By forming the electrodes on the slant, when the voltage is not applied, all of the liquid crystal molecules between the two alignment layers 59, 62 are aligned parallel to the substrates 26, 27 and to the principal transmission axis  $\theta_{PL2}$  of analyzer. Therefore, the viewing angle inverted areas appear at the corners of the display so that the inverted phenomenon is not remarkable. The liquid crystal is nematic without the need to mix a chiral dopant. The LCD shown in FIG. 2(a) is a normally black mode because the polarizer and the analyzer are crossed and the liquid crystal molecules between them are parallel to one another.

**Page 11, paragraph one, starting with line 1.**

electric field is weaker as the distance increases from the first substrate formed with electrodes 48 and 49. The irregularities in the electric field can be achieved by making the thickness of the liquid crystal layer greater than the interval between two electrodes.

**Page 13, paragraph one, starting with line 1.**

$\Delta n d = (85^\circ/90^\circ)\lambda = 0.94$ . The dielectric anisotropy  $\Delta n$  and the thickness  $d$  of the liquid crystal are appropriately arranged. The dielectric anisotropy of the liquid crystal generally used in TN mode is 0.06-0.08, and the wave length of the light is  $0.56\mu\text{m}$ . When the values are substituted in the above formula, the thickness  $d$  should be  $6.0\text{-}8.8\mu\text{m}$ .

**Page 16, paragraph two, starting with line 16.**

In the above structure, the extension line  $\theta_{EL}$  is disposed  $95^\circ$  relative to the horizontal line ( $0^\circ$ ), such that the electric field direction  $\theta_{FE}$  is  $5^\circ$ . The extension line is extended from

the  $5\mu\text{m}$  width data electrode 48 and the  $5\mu\text{m}$  width common electrode 49, which are parallel to each other with a  $5\mu\text{m}$  space therebetween.

**Page 17, paragraph one, starting with line 1.**

to a thickness of about  $8\mu\text{m}$  and baking. The alignment layer 59 coated on the first substrate 27 is rubbed in the  $-90^\circ$  direction, and the alignment layer 62 coated on the second substrate 26 is rubbed in the  $90^\circ$  direction. The spacer 65 can be formed from Micropal (produced in SEKISUI FINE CHEMICAL CO.) with an exemplary  $8.0\mu\text{m}$  diameter, to maintain the liquid crystal layer 60 with a mean thickness of  $7.8\mu\text{m}$ . The liquid crystal material can be ZGS 5025 ( $\Delta n=0.067$ ;  $\Delta \epsilon=6.0$ ; produced by CHISSO CO.). The pretilt angle of the liquid crystal is  $4.8^\circ$ , and the retardation value  $\Delta n d$  is 0.41.

The principal transmittance axis of the polarizer 63 attached on the first substrate 27 is the horizontal direction ( $\theta_{PL1}=0^\circ$ ) and that of the analyzer 64 attached on the second substrate 26 is the vertical direction ( $\theta_{PL2}=90^\circ$ ).

**Page 19, paragraph one, starting with line 5.**

The rotation angle of the liquid crystal layer is detected by an evaluator for LCD (produced in NIHON DENSHI CO.). The results show that the liquid crystal molecules  $1\mu\text{m}$  distant from the second substrate 26 have a optic axis of  $88^\circ$ , and the liquid crystal molecules  $1\mu\text{m}$  distant from to the first substrate 27 have a optic axis of  $19^\circ$ . It can be understood that the alignment direction of the liquid crystal molecules near the first substrate 26 is almost fixed, but the alignment direction of the liquid crystal molecules near the first substrate 27 is rotated about the anticipated angle. At this position, the anticipated angle of the liquid crystal molecules is 16. Therefore, the liquid crystal molecule is twisted in the liquid crystal layer.

**Page 20, paragraph one, starting with line 1.**

The embodiments of the present invention have been described as having a 95° electrode extension line as an example. However, the direction can be selected according to the viewing angle characteristics that are required.

**IN THE CLAIMS:**

Please cancel claims 1-27 without prejudice or disclaimer of the subject matter contained therein.

Please ADD new claim 28.

28. (New) A liquid crystal display device comprising:

a first substrate having a first surface;

a second substrate having a second surface;

a liquid crystal layer formed adjacent to the first surface and the second surface;

at least one pair of electrodes formed adjacent to said first surface;

wherein a distance between the pair of electrodes is greater than the thickness of the liquid crystal layer.

102201 0833650

**REMARKS**

Claims 28 is now pending in the present application. Claims 1-27 have been cancelled without prejudice and new claims 28 has been added. Examination and consideration of the application, as amended, are respectfully requested.


If these papers are not considered timely filed by the Patent and Trademark Office, then a petition is hereby made under 37 C.F.R. §1.136, and any additional fees required under 37 C.F.R. §1.136 for any necessary extension of time, or any other fees required to complete the filing of this response, may be charged to Deposit Account No. 50-0911 (8733.036.11). Please credit any overpayment to deposit Account No. 50-0911. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

LONG, ALDRIDGE & NORMAN, LLP

SKJ/dlt

By: \_\_\_\_\_

  
Song K. Jung  
Reg. No. 35,210

701 Pennsylvania Avenue, N.W.  
Sixth Floor, Suite 600  
Washington, D.C. 20004  
Telephone No.: (202) 624-1200  
Facsimile No.: (202) 624-1298  
Date: October 22, 2001

FOR "PATENT" DEPOSIT

**MARKED UP VERSION OF THE ABSTRACT OF THE DISCLOSURE**

A liquid crystal display including: a first transparent substrate coated with a first alignment layer, a second transparent substrate coated with a second alignment layer, the second substrate facing the first transparent substrate, a liquid crystal layer between the substrates, a polarizer attached on the outer surfaces of the substrates, a pair of electrodes formed on the first substrates, and a driving circuit applying signal voltage to the electrodes. The liquid crystal molecules adjacent to the first substrate is rotated by applying the voltage, but, the liquid crystal molecule adjacent to the second substrate is fixed regardless of the applied voltage. The electrode pair, substantially straight data and common electrodes, are inclined at an angle with respect to a gate line.

[illegible][illegible]

09663070

[illegible]

096630  
096631  
096632  
096633  
096634  
096635  
096636  
096637  
096638  
096639  
096640  
096641  
096642  
096643  
096644  
096645  
096646  
096647  
096648  
096649  
096650  
096651  
096652  
096653  
096654  
096655  
096656  
096657  
096658  
096659  
096660  
096661  
096662  
096663  
096664  
096665  
096666  
096667  
096668  
096669  
096670  
096671  
096672  
096673  
096674  
096675  
096676  
096677  
096678  
096679  
096680  
096681  
096682  
096683  
096684  
096685  
096686  
096687  
096688  
096689  
096690  
096691  
096692  
096693  
096694  
096695  
096696  
096697  
096698  
096699

[illegible][illegible]

**Page 6, paragraph 5, starting with line 16.**

FIG. 4a shows a plan view of the liquid crystal display according to the present invention, and Fig. 4b shows a cross-section of the device taken along the line [IVA-IVA] IV-IV of Fig. 4a;

**Page 8, paragraph two, starting with line 12.**

The liquid crystal molecules [60] 78 will be twisted between the two substrates 26, 27 by applying the driving voltage to the electrodes 48, 49. The distance between two adjacent electrodes 48, 49 is less than the thickness of the liquid crystal layer 60. The retardation value is calculated by following formula:

**Page 9, paragraph one, starting with line 3.**

FIG. 3 shows optical axes of the liquid crystal display according to the present invention.  $\theta_{EL}$  is represented as the extension direction of the electrodes 48 and 59,  $\theta_{FE}$  is the electric field direction applied by the electrodes,  $\theta_{LC1}$  is the optical axis direction of the liquid crystal molecules adjacent to the first substrate and  $\theta_{LC2}$  is the optical axis direction of the liquid crystal molecules adjacent to the second substrate when the voltage is not applied.  $\theta_{PL1}$  is the [principle] principal transmission axis of a polarizer,  $\theta_{PL2}$  is the [principle] principal transmission axis of an analyzer,  $\theta_{LC1}$  is the optical axis direction of the liquid crystal molecules adjacent to the first substrate when the voltage is applied. The alignment direction  $\theta_{LC1}$  of the first substrate is anti-parallel to the alignment direction  $\theta_{LC2}$  of the second substrate, and the [principle] principal transmission axis  $\theta_{PL2}$  of the analyzer is parallel to the alignment direction  $\theta_{LC1}$ ,  $\theta_{LC2}$ . In addition, the principle transmission axis  $\theta_{PL1}$  of the polarizer is perpendicular to the [principle] principal transmission axis  $\theta_{PL2}$  of the analyzer.

0998330 102201

**Page 10, paragraph one, starting with line 3.**

By forming the electrodes on the slant, when the voltage is not applied, all of the liquid crystal molecules between the two alignment layers 59, 62 are aligned parallel to the substrates 26, 27 and to the [principle] principal transmission axis  $\theta_{PL2}$  of analyzer. Therefore, the viewing angle inverted areas appear at the corners of the display so that the inverted phenomenon is not remarkable. The liquid crystal is nematic without the need to mix a chiral dopant. The LCD shown in FIG. 2(a) is a normally black mode because the polarizer and the analyzer are crossed and the liquid crystal molecules between them are parallel to one another.

**Page 11, paragraph one, starting with line 3.**

electric field is weaker as the distance increases from the first substrate formed with electrodes 48 and 49. [Irregularities] The irregularities in the electric filed can be [avoided] achieved by making the thickness of the liquid crystal layer greater than the interval between two electrodes.

**Page 13, paragraph one, starting with line 1.**

[ $\Delta n d = 0.74\lambda$ ]  $\Delta n d = (85^\circ/90^\circ)\lambda = 0.94$ . The dielectric anisotropy  $\Delta n$  and the thickness  $d$  of the liquid crystal are appropriately arranged. The dielectric anisotropy of the liquid crystal generally used in TN mode is 0.06-0.08, and the wave length of the light is  $0.56\mu\text{m}$ . When the values are substituted in the above formula, the thickness  $d$  should be [5.0-7.0] 6.0-8.8 $\mu\text{m}$ .

**Page 16, paragraph two, starting with line 16.**

In the above structure, the extension line  $\theta_{EL}$  is disposed  $95^\circ$  relative to the horizontal line [(0°)] (0°), such that the electric filed direction  $\theta_{FE}$  is  $5^\circ$ . The extension line is extended

from the  $5\mu\text{m}$  width data electrode 48 and the  $5\mu\text{m}$  width common electrode 49, which are parallel to each other with a  $5\mu\text{m}$  space therebetween.

**Page 17, paragraph one, starting with line 1.**

to a thickness of about  $8\mu\text{m}$  and baking. The alignment layer 59 coated on the first substrate 27 is rubbed in the  $-90^\circ$  direction, and the alignment layer 62 coated on the second substrate 26 is rubbed in the  $90^\circ$  direction. The spacer 65 can be formed from Micropal (produced in SEKISUI FINE CHEMICAL CO.) with an exemplary [6.4]  $8.0\mu\text{m}$  diameter, to maintain the liquid crystal layer 60 with a mean thickness of [6.2]  $7.8\mu\text{m}$ . The liquid crystal material can be ZGS 5025 ( $\Delta n=0.067$ ;  $\Delta \epsilon=6.0$ ; produced by CHISSO CO.). The pretilt angle of the liquid crystal is  $4.8^\circ$ , and the retardation value  $\Delta n d$  is 0.41.

The [principle] principal transmittance axis of the polarizer 63 attached on the first substrate 27 is the horizontal direction ( $\theta_{PL1}=0^\circ$ ) and that of the analyzer 64 attached on the second substrate 26 is the vertical direction ( $\theta_{PL2}=90^\circ$ ).

**Page 19, paragraph one, starting with line 5.**

The rotation angle of the liquid crystal layer is detected by an evaluator for LCD (produced in NIHON DENSHI CO.). The results show that the liquid crystal molecules [adjacent]  $1\mu\text{m}$  distant from the second substrate 26 have a [transmittance] optic axis of  $88^\circ$ , and the liquid crystal molecules [adjacent to]  $1\mu\text{m}$  distant from to the first substrate 27 have a [transmittance] optic axis of  $19^\circ$ . It can be understood that the alignment direction of the liquid crystal molecules near the first substrate 26 is almost fixed, but the alignment direction of the liquid crystal molecules near the first substrate 27 is rotated about the anticipated angle [of  $16^\circ$ ]. At this position, the anticipated angle of the liquid crystal molecules is 16. Therefore, the liquid crystal molecule is twisted in the liquid crystal layer.

**Page 20, paragraph one, starting with line 1.**

The embodiments of the present invention have been described as having a 95°  
[electric field] electrode extension line as an example. However, the direction can be selected  
according to the viewing angle characteristics that are required.

09/678,241 "102201" 02228560